

## RACING OIL 5W-50

## **Product Description:**

**RACING OIL 5W-50** is a high performance motor oil based on 100% synthetic technology with exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fueled engines in passenger cars with or without turbocharger, working under severe temperature and load conditions.

**RACING OIL 5W-50** is based on high quality synthetic base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

**RACING OIL 5W-50** meets the following performance criteria:

API SN MB 229.1 ACEA A3/B4

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-50
Density@15°C	kg/m³	ASTM D4052	853
Kin. Viscosity @40°C	mm²/s	ASTM D7042	112
Kin. Viscosity @100°C	mm²/s	ASTM D7042	18.5
Viscosity Index		ASTM D2270	186
Viscosity CCS @-30°C, max	сР	ASTM D5293	5660
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	10.2
Sulpated Ash	%Wt	ASTM D874	1.09

**Product Nr:** 42020 **Date Issued:** 10-12-2019

**Date Superseded:** 15-01-2018 **Revision nr:** 02

