



# SUPER TRACTOR OIL

## 15W-40

### Product Description:

**SUPER TRACTOR OIL 15W-40** is a high quality so called “Super Tractor Oil Universal” (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed “wet brakes”. This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).

**SUPER TRACTOR OIL 15W-40** is formulated on mineral base stocks in combination with an unique additive package to reach the following properties;

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

**SUPER TRACTOR OIL 15W-40** meets the following performance criteria:

<b>Engine Spec</b>	<b>API CG-4/CF-4/CE/SF</b>	<b>MB 228.1</b>	<b>ACEA E3</b>	
<b>UTTO Spec</b>	<b>Ford M2C134-A</b>	<b>Ford M2C159B/C</b>	<b>FNH 82009203</b>	<b>Allison C-4</b>
	<b>Cat TO-2</b>	<b>API GL-4</b>	<b>JD J27</b>	<b>ZF TE-ML 6B/C, 7B/D</b>
<b>Hydr Spec</b>	<b>Eaton M-2950S</b>	<b>Eaton 1-280-S</b>	<b>Danfoss</b>	

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	876
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	95
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	142
Viscosity CCS @-20°C, max	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	10.6

**Product Nr:** 43290  
**Date Superseded:** 04-12-2018

**Date Issued:** 12-12-2019  
**Revision nr:** 03

